

**GC128-M**  
**GC128-H**  
**GC128-B**

This single needle high speed lockstitch sewing machine series uses a link take up, rotating hook and link driven feed mechanism, thereby allowing it to maintain precise stitching even when changing between low and high speed as well as forward and reverse stitching. The arm shaft and hook are driven by bevel gears which ensures quality stitch appearance. The dial operated stitch regulator makes it easy to adjust and maintain stitch length. The different subclasses can be used to sew light and medium weight materials up to and including medium-heavy weight materials such as leather, canvas, plastics, etc.



Model		GC128-M	GC128-H	GC128-B	GC128-HL	GC128-BL
Max Sewing Speed		5000 rpm	3500 rpm	3000 rpm	3500 rpm	3000 rpm
Stitch length		0-5 mm	0-7 mm	0-8 mm	0-7 mm	0-8 mm
Needle bar stroke		31.8 mm	35 mm	35 mm	35 mm	35 mm
Presser foot lift	By hand	5.5 mm	6 mm	6 mm	6 mm	6 mm
	by knee	13 mm	13 mm	13 mm	13 mm	13 mm
Needle Size		DB x 1 9#-16#	DP x 5 18#-24#	DP x 5 18#-24#	DP x 5 18#-24#	DP x 5 18#-24#
Feed Dog		3 rows of teeth			15 Roller presser foot	

Rotating Hook	Auto lubricated hook	Auto lubricated large hook	Auto lubricated hook	Auto lubricated large hook
Lubrication	Auto lubricated			
Motor	370W Clutch motor			